

Epoxy RFID/NFC Mini Tag




Application:

- Product Authentication
- Tools / Instruments Locator
- Asset Management
- Miniature Tag Applications

Key Features

- Robust Waterproof, Dustproof for industrial environment,
- Flexible RFID protocol, Frequencies with adjustable performance,
- Customized Code printing and encoding
- Easily integrated for industrial Identification applications

Tag Spec.:

Chip:	 NXP ICODE/ MIFARE Classic®	Color:	Black or custom
Size& Thickness:	15*3mm /18*5mm / Customized	IP Class:	IP67
Material	PPS housing + Epoxy	Neight Weight:	Appr 1.5g
Operating Temperature:	-10 to +60°C	Storage Temperature:	-25 to +85°C
Read range	10 ~ 50 mm	Protocal	ISO 14443 / ISO 15693 / ISO18092

Additional Craft for Optional:

Coding:	Chip Encoding
ID Number Printing:	Laser engrave
On Metal:	Anti-Metal Ferrite Layer optional, Thickness from 0.3-0.5mm
Adhesive:	Ordinary Adhesive sticker, 3M Adhesive Layer Optional
Packing:	Flod up Heat-Shrinkable Packing
Warranty:	1 year



The information contained on this Document is considered to be confidential material proprietary to JYL-Tech, and this information shall not be disclosed, duplicated or copied for any purpose, Nor made available for any third party without the prior consent to JYL-Tech.